



MONOCURE 3D3583W 3D STANDARD WHITE PHOTO-REACTIVE RESIN

END USE

Monocure 3D standard photo-reactive white resin has been designed to use in SLA & projector type DLP 3D Printers for UV wavelengths up to 420nm. The solid white appearance allows you to Print models or parts with a detailed smooth finish that could be painted if required.

PHYSICAL PROPERTIES

Colour	Solid White
Viscosity	500 - 600cps @ 25°C (Brookfield RVT)
Odour	Negligible Characteristics
Shelf Life	12 months
Active Solids	100%
UV Cure	225nm to 420nm
Cure Speed	Fast with UV Lasers & Projectors
Storage	Dark Cool, dry place out of direct sunlight.
Wash Up	IPA (Isopropyl Alcohol)



APPLICATION:

Stereolithography (SLA) is an additive manufacturing process that employs a vat of liquid ultraviolet curable photopolymer resin and an ultraviolet laser to build parts' layers one at a time. For each layer, the laser beam traces a cross-section of the part pattern on the surface of the liquid resin. Exposure to the ultraviolet laser light cures and solidifies the pattern traced on the resin and joins it to the layer below.

Digital Light Projection (DLP) is similar to SLA however it uses a digital light projector to harden the resin instead of a laser. The main advantages are that it can harden a whole layer in a lot less of the time it takes to a laser to trace around and fill in each item on the print bed.

PACKAGING:

Monocure 3D3583W is packed in 500ml, 1ltr & 5ltr black plastic containers with a screw top cap.